Particle Identification I

ICFA 2002
Morelia, Mexico, November 25/26, 2002

Jürgen Engelfried[1]
Instituto de Física, Universidad Autónoma de San Luis Potosí, Mexico

Outline

- Introduction
- Transition Radiation Detectors
- Ring Imaging Cherenkov Detectors – RICH
- Summary

[1]jurgen@ifisica.uaslp.mx, http://www.ifisica.uaslp.mx/~ jurgen

Tom Ypsilantis 1928-2000

Introduction

In this class: Only identification of charged particles

What is Particle Identification?

Two major applications:

1. Beam Particle Identification (Fixed Target)
2. Identification of decay products

In both cases the momentum of the particle is known

1. By beamline elements (only small momentum bin)
2. Measured by a magnetic spectrometer (wire chambers)

$\Longrightarrow$ Particle Identification reduces to measure the velocity (this class) or the total energy (calorimetry class) or specific energy loss (dE/dx).

First some Physics Example...

Reconstruction of Λ_c^+

- Λ_c^+ baryon consists of (udc) quarks
- Mass $m_0 = 2.284.9\,\mathrm{GeV}/c^2$ (remember: proton $0.938\,\mathrm{GeV}/c^2$)
- Lifetime: $\tau = 2.0 \cdot 10^{-13}\,\mathrm{sec}$
- Decays to $\Lambda_c \to pK^-\pi^+$ in 5.0 % of the time.
- Only in 1 out of 1000 collisions a charm quark gets produced.

Special Theory of Relativity:

$$
\begin{aligned}
E &= m \cdot c^2 \\
m &= m_0 \cdot \gamma \\
\gamma &= \frac{1}{\sqrt{1 - \frac{v^2}{c^2}}} = \frac{E \cdot c^2}{m_0} \\
p &= m \cdot v \approx m_0 \cdot \gamma \cdot c \\
\text{Time dilation:} \quad t &= t_0 \cdot \gamma \\
\text{Mean flight path:} \quad L &= c \cdot \tau \cdot \gamma
\end{aligned}
$$

$\Longrightarrow$ A Λ_c^+ with momentum $200\,\mathrm{GeV}/c$ flies on average 5.4 mm

$\Longrightarrow$ Do a Fixed Target Experiment – But even there we cannot observe a Λ_c directly

What do we do?

- Measure type, direction, momentum, and charge of all decay products
- Apply momentum and energy conservation to "interesting" decay vertex and calculate energy and momentum of hypothetical mother particle
- Transform into rest system of mother particle to obtain rest mass
- Do this for a lot of events, fill histogram with results

Measuring direction and decay vertex

- Use silicon microstrip detectors

Measuring momentum and charge

- Deflection in magnetic field, measure track angles before and after with wire chambers

Measuring type (is it a proton?)

- Measure total energy in calorimeter, calculate mass
- Measure velocity with Cherenkov effect



Fig. 8: $\Lambda_c^+ \to pK^-\pi^+$ event - vertex view


Y
YZ−view
Run: 10439 Event:100034284
63.00
0.00
−63.00
Z
−40.00
590.00
1220.00


X
XZ−view
63.00
0.00
−63.00
Z
−40.00
590.00
1220.00


Date: 98/10/08 22.59.43
Run: 10439 Spill: 41 Event_in_Spill: 17156 Event: 100034284 Tubes: 63
18
17
19
16
Tracks : 16 17 18 19
Momenta: -095 +154 +074 -153
Masses: Sigma Proton Kaon Pion Muon Electron Backgrnd


PRELIMINARY SELEX Production Comparison
Sample cuts: x_F>0.3 and L/σ>8
$\bar{\Lambda}_c^-/\Lambda_c^+$=0.1
Σ^-
$\bar{\Lambda}_c^-/\Lambda_c^+$=0.6
π^-
$\bar{\Lambda}_c^-/\Lambda_c^+$=0.1
p
$\bar{D}^-/D^+$=1.4
Σ^-
$\bar{D}^-/D^+$=1.3
π^-
$\bar{D}^-/D^+$=1.2
p
Events/10 [MeV/c²]
Mass [GeV/c²]

"Simple" Methods of Particle Identification
Time–of–flight (TOF)

- Put two Scintillation Counters at a known distance
- Measure time difference between the two signals

Good time resolution: 150 psec.
Maximum distance: ≈ 10 m (detector), ≈ 100 m (beamline).
$\Longrightarrow$ Can measure difference between Kaons and Pions up to a few GeV/c
Also has problem at higher rate and/or multiple particles hitting the same scintillator

Radiation by Charged Particles

Radiation is emitted by a charge particle if:

1. $v > c/n$: Cherenkov radiation
2. $\vec{v}/c_{\rm ph} = \vec{v} \cdot n/c$ changes
   (a) $|\vec{v}|$ changes: Bremsstrahlung
   (b) direction of $\vec{v}$ changes: Synchrotron radiation
   (c) n changes: Transition Radiation

Transition Radiation Detectors (TRD)

Transition Radiation: Reformation of particle field while traveling from medium with $\epsilon = \epsilon_1$ to medium with $\epsilon = \epsilon_2$.

Energy of radiation emitted at a single interface

$$S = \frac{\alpha\hbar Z^2}{3}\frac{(\omega_1 - \omega_2)^2}{\omega_1 + \omega_2}\gamma$$

$\alpha = 1/137$, ω_1, ω_2 plasma frequencies, $\gamma = E/mc^2$.
Typical values: Air $\omega_1 = 0.7\,\mathrm{eV}$, polypropylene $\omega_2 = 20\,\mathrm{eV}$

Spectral and angular dependence of Transition Radiation:

$$\frac{d^2}{d\vartheta d\omega} = \frac{2e^2}{\pi c}\left(\frac{\vartheta}{\gamma^{-2} + \vartheta^2 + \omega_1^2/\omega^2} - \frac{\vartheta}{\gamma^{-2} + \vartheta^2 + \omega_2^2/\omega^2}\right)^2$$

$\Longrightarrow$ Most of radiation in cone with half angle $1/\gamma$: forward in particle direction.



- Large photon energies $\omega > \gamma\omega_2 \approx 20 - 30\,\mathrm{KeV}$: large drop of intensity $\propto \gamma^4/\omega^4$
- Medium energies $\gamma\omega_1 < \omega < \gamma\omega_2$: Logarithmic decrease with ω
- Small energies $\omega < \gamma\omega_1 \approx 1\,\mathrm{KeV}$: intensity almost constant

Probability to emit a KeV photon: $\approx 10^{-2} \Longrightarrow$ Need a lot of interfaces: stack of radiator foils.
Consequences:

- Need minimum foil thickness so particle field reaches new equilibrium
- Transition $\omega_1 \to \omega_2$ and $\omega_2 \to \omega_1$ equal $\Longrightarrow$ Interference effects (min and max in fig)
- Equally spaced foils: Interference between amplitude of different foils
- Finite thickness of foils: re-absorption of radiation ($\propto Z^5$): Low Z materials.

Typical values used in TRDs:
Thickness: $30\,\mu$m, distance: $300\,\mu$m,
materials: mylar, CH_2, carbon fibers, lithium.

Detection of Transition Radiation

X-rays emitted under small angle to particle track

$\Longrightarrow$ X-ray detector sees X-rays and particle dE/dx together.

Typical dE/dx in gas detectors: some KeV/cm and Landau distributed

$\Longrightarrow$ Signals from dE/dx and X-ray similar

Detector: Use "thin" MWPC, with Xenon or Krypton, several (10) radiator / chamber units to beat Landau





Fig 4. Schematic of a radiator-chamber module showing the final design parameters discussed in the text.

Two identification methods: Charge integration, Cluster counting


BEAM TRD


BEAM TR


RUN 7747 Trigger BEAM
ID 47021
Entries 50000
Σ⁻ 600 GeV
π- 600 GeV
Number of BTRD planes ON, raw data
ID 47101
Entries 13666
Σ⁻ 600 GeV
π- 600 GeV
Number of BTRD planes ON, one track events
RUN 8996 Trigger BEAM
Σ/π 600 GeV
Nmb BTRD ON
Likelihood
Σ eff. %
π eff. %

ATLAS Transition Radiation Tracker (TRT)



Length:	Total	6802 cm	N straws:	Total	372032
	Barrel	148 cm		Barrel	52544
	End-cap	257 cm		End-cap	319488
Outer diameter		206 cm	N electronics channels		424576
Inner diameter		96-128 cm	Weight		~ 1500 kg

Fig. 11. ATLAS Transition Radiation Tracker (TRT) conceptual design [2].



Fig. 8. The detected number of the TR photons for different Lorentz factors [4].

Cherenkov Radiation

A charged particle with a velocity v larger than the velocity of light in a medium emits light.

Angle of emmission:
$$\cos\theta_c = \frac{1}{\beta\, n} = \frac{1}{\frac{v}{c}\, n}$$

Number of photons:
$$\frac{d^2N}{dEdl} = \frac{\alpha}{\hbar c}\left(1 - \frac{1}{(\beta n)^2}\right) = \frac{\alpha}{\hbar c}\sin^2\theta_c$$
$$\frac{d^2N}{d\lambda dl} = \frac{2\pi\alpha}{\lambda^2}\sin^2\theta_c$$

First (obvious) application: Threshold Cherenkov Detectors

For fixed momentum and only 2 particles to separate (beam line)

More than 2 particles and/or wider momentum range: Several counters at different thresholds

NUCLEAR INSTRUMENTS AND METHODS 9 (1960) 55–66; NORTH-HOLLAND PUBLISHING CO.

A NEW TYPE OF ČERENKOV DETECTOR FOR THE ACCURATE MEASUREMENT OF PARTICLE VELOCITY AND DIRECTION*

ARTHUR ROBERTS

Department of Physics[1], University of Rochester

Received 22 June 1960

A new type of Čerenkov radiation detector is proposed, in which the light emitted by a single particle traversing a radiator is imaged by means of a lens or mirror focused at infinity, on the cathode of an image-intensifier tube. The image is a ring, whose diameter measures accurately the Čerenkov cone angle and thus the particle velocity. In addition the coordinates of the center of the circular image accurately indicate the orientation of the particle trajectory through the system. The sensitivity of presently available systems of cascaded image-intensifier tubes allows the photographic recording of the image produced by a single particle. The system is inherently insensitive to background noise. It can observe simultaneously several incident particles whose directions span a wide angle. It may be gated with microsecond coincidence resolving times. It can use condensed or gaseous radiators. With the former, chromatic dispersion is likely to limit the accuracy. For gas radiators, the attainable accuracy of velocity determination is estimated as $\Delta\beta = \pm 0.002$ or better. The accuracy of track orientation ± 0.001 radians. The range of velocity and orientation simultaneously observable depends on the angular field of view of the objective. Sources of error, the precision attainable, the design of practical systems and some possible applications are discussed.

1. Introduction

The Čerenkov light emitted by a fast-moving particle consists of rays parallel to the elements of a right circular cone. As observed by a detector, it seems to originate from a ring source at infinity, whose angular diameter is that of the cone [see fig. 1]. It has justly been likened to the light from a ring of faint stars. If such light is collected by a telescope objective, an image of the ring is formed in the focal plane with a diameter given by

$$d = 2f\tan\theta \qquad (1)$$

where f is the focal length of the objective, and θ the half-angle of the cone of light.

Precisely such an arrangement may be used to collect the Čerenkov radiation from a fast particle, as shown in fig. 2. The light emitted by the particle may all be collected in a ring image. In principle, a photographic plate could then record the particle's passage, but the light emitted is of course far too weak to allow the photography of single particles. However, existing image-intensifier tubes, as now used in cascade for scintillation track-imaging, can record such ring images. Fig. 3 shows such a cascade system.



(a) (b)

Fig. 1. (a) Čerenkov radiation emitted by a fast particle traversing a radiator is seen as a circular cone of parallel rays coincident with the particle path. (b) The light from a distant ring source, after passage through an optical system, is a cone of parallel light which may be focused to a ring image by a lens or mirror objective.

One can construct in this way a Čerenkov detector that measures accurately both the particle velocity,—even at very high speeds ($\beta = 0.98$),—and the direction of motion of the particle. Furthermore, these measurements may be made on particles entering a large radiator at

NUCLEAR INSTRUMENTS AND METHODS 142 (1977) 377–391 ; © NORTH-HOLLAND PUBLISHING CO.

PHOTO-IONIZATION AND CHERENKOV RING IMAGING

J. SEGUINOT* and T. YPSILANTIS*

CERN, Geneva, Switzerland

Received 17 December 1976

We have investigated the photo-ionization process in gases and shown that single photon pulse counting in multiwire proportional chambers (MWPC) is possible with about 50% quantum efficiency for photons above 9.5 eV. An application of this technique in imaging the Cherenkov ultra-violet (UV) radiation is presented.

1. Introduction

The Cherenkov radiation effect in an optical medium allows a precise determination of the velocity β (or $\gamma = (1-\beta^2)^{-\frac{1}{2}}$) of a charged particle passing through the medium. From the Cherenkov relation[1]

$$\cos\theta = 1/\beta n, \tag{1}$$

where θ is the emission angle of the Cherenkov light and n the refractive index of the optical medium, we find

$$\frac{\Delta\gamma}{\gamma} = \left[\tan^2\theta\,(\Delta\theta)^2 + \left(\frac{\Delta n}{n}\right)^2\right]^{\frac{1}{2}}, \tag{2}$$

with $\Delta\beta$, $\Delta\theta$ and Δn the r.m.s. error in the measurement of β, θ and n respectively. Litt and Meunier[2] show that with a "differential isochronous self collimating" type Cherenkov counter (DISC) a resolution of $\Delta\beta/\beta = 10^{-5}$ is possible. This corresponds to a γ resolution of $\Delta\gamma/\gamma = \Delta\beta/\beta = 0.4\%$ at $\gamma = 200$. In such counters the Cherenkov photons emitted at different points along the particle's straight line trajectory are focused by a reflective mirror (radius R, focal length $f = \frac{1}{2}R$) to give a circular ring image of radius r at the mirror focal plane. In the small angle approximation the focal surface is a plane and the radius of the ring image is

$$r = f\tan\theta. \tag{3}$$

The angle determination in a DISC is obtained by using an annular diaphragm of radius r at the mirror focal plane. Photomultipliers (PMs) located behind the diaphragm detect the transmitted photons. For optimal resolution no additional optical elements are used between the diaphragm and the PMs. Obviously a DISC type counter can only be used in collimated beams so that the source of Cherenkov radiation is along the optical axis of the device. Furthermore, the counter is not continuously sensitive in β and responds only to particles having a preset value of β (i.e. Cherenkov light which passes through the annulus). Such counters are suitable for velocity (mass) selection in collimated (momentum analyzed) primary particle beams but completely unsuitable for velocity measurement of secondary particles emerging from an interaction. The phase space occupied by these particles is large whereas the phase space acceptance of DISC is small.

A secondary particle detector may be imagined (see fig. 1) as consisting of a spherical mirror of radius R whose centre is the source of secondary particles (target) and a spherical detector surface at radius $\frac{1}{2}R$ with the Cherenkov radiating medium



Ring Imaging Cherenkov – The Basics



$$\cos\theta_c = \frac{1}{\beta \cdot n}$$

$$r = F \cdot \theta_c = \frac{R}{2} \cdot \theta_c$$

$$N_{ph} = N_0 \cdot L \cdot \sin^2\theta_c$$

θ_c: Cherenkov angle
β: velocity
n: refractive index
r: Radius of ring on focal surface
R: Radius of curvature of spherical mirror(s)
F: Focal length ($F = R/2$)
L: Radiator length (usually $L = F$)

Parallel particles have the same ring image



$$r = \frac{R}{2}\sqrt{2 - \frac{2}{n}\sqrt{1 + \frac{m^2c^2}{p^2}}}$$



1 3 5 4 2 6

SELEX RICH: Particle Id negative tracks



Short History of RICHes

First Generation: Beginning of 1980's.
Examples: Omega RICH (WA69, WA82), E653 RICH.

Second Generation: End-of 80's beginning of 90's.
Examples: Upgraded Omega RICH (WA89, WA94), Delphi, SLD–GRID, CERES.

Third Generation: Mid-End 90's.
Examples: SELEX RICH, Hermes, Hera-B.

New Generation: BaBar–DIRC, PHENIX, CLEO–III, COMPASS

Future: ALICE, LHC–B, BTeV, CKM, ...

RICH – The Reality

- Center of ring depends on track angle $\Longrightarrow$ large detector surface (up to square meters)
- good resolution of photon position $\Longrightarrow$ large number of "pixels" (up to 100000 or more)
- Spectrum of Cherenkov photons

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha}{\lambda^2} L \sin^2\theta_c$$

  $\Longrightarrow$ Ultraviolet
- refractive index $n = n(\lambda) \Longrightarrow$ Chromatic dispersion
- Detection of UV-photons: convert photon in electron (photoeffect)
  1. small (up to a few thousand) number of pixels: Photomultipliers
  2. large number of pixels or area: Time Expansion Chambers with TEA or TMAE
- When using TEC: particle pass through the chambers: dE/dx
- When using TEC: response (memory) time limit rate


Distribation of Ring Centers
z (cm)
20
0
-20
p
K⁻
A⁺ ≡ Ξ_c⁺
→ Λ K⁻ π⁺ π⁺
Lo ρ π⁻
z (cm)
20
0
-20
p
K⁻
Ω_c
→ Ξ⁻ K⁻ π⁺ π⁺
Lo Λ π⁻
z (cm)
20
0
-20
p
p̄
Ū⁺
→ Λ p̄ π⁺ π⁺
-60 -40 -20 0 20 40 60 80 y (cm)
WA89 Proposal
Fig. 20

RICH – The Reality

- Center of ring depends on track angle $\Longrightarrow$ large detector surface (up to square meters)
- good resolution of photon position $\Longrightarrow$ large number of "pixels" (up to 100000 or more)
- Spectrum of Cherenkov photons

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha}{\lambda^2} L \sin^2\theta_c$$

  $\Longrightarrow$ Ultraviolet
- refractive index $n = n(\lambda) \Longrightarrow$ Chromatic dispersion
- Detection of UV-photons: convert photon in electron (photoeffect)
  1. small (up to a few thousand) number of pixels: Photomultipliers
  2. large number of pixels or area: Time Expansion Chambers with TEA or TMAE
- When using TEC: particle pass through the chambers: dE/dx
- When using TEC: response (memory) time limit rate


Radius [cm]
e
μ
π
K
p
Momentum [GeV/c]
μ-π
e-π
π-K
π-p
Difference [cm]
2σr multitrack events
2σr single track events
Momentum [GeV/c]

RICH – The Reality

- Center of ring depends on track angle $\Longrightarrow$ large detector surface (square meters)
- good resolution of photon position $\Longrightarrow$ large number of "pixels" (100000)
- Spectrum of Cherenkov photons

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha}{\lambda^2} L \sin^2\theta_c$$

  $\Longrightarrow$ Ultraviolet
- Refractive index $n = n(\lambda) \Longrightarrow$ Chromatic dispersion
- Detection of UV-photons: convert photon in electron (photoeffect)
  1. small (up to a few thousand) number of pixels: Photomultipliers
  2. large number of pixels or area: Time Expansion Chambers with TEA or TMAE
- When using TEC: particle pass through the chambers: dE/dx
- When using TEC: response (memory) time limit rate


Nitrogen, 1atm
Refractive Index (n-1)*10^6
800
700
600
500
400
300
200
100
0
100
150
200
250
300
350
400
450
500
Wavelength [nm]


Neon, 1atm
Refractive Index (n-1)*10^6
140
120
100
80
60
40
20
0
100
150
200
250
300
350
400
450
Wavelength [nm]

RICH – The Reality

- Center of ring depends on track angle $\Longrightarrow$ large detector surface
- good resolution of photon position $\Longrightarrow$ large number of "pixels" (100000)
- Spectrum of Cherenkov photons

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha}{\lambda^2} L \sin^2\theta_c$$

  $\Longrightarrow$ Ultraviolet
- refractive index $n = n(\lambda) \Longrightarrow$ Chromatic dispersion
- Detection of UV-photons: convert photon in electron (photoeffect)
  1. small (up to a few thousand) number of pixels: Photomultipliers
  2. large number of pixels or area: Time Expansion Chambers with TEA or TMAE
- When using TEC: particle pass through the chambers: dE/dx
- When using TEC: response (memory) time limit rate



Figure 13: Photon transmission and photoionisation quantum efficiency for various CRID materials as function of photon energy in the UV range. (Reproduced from


TMAE and Quartz
Transmission, Quantumefficiency
Wavelength [nm]
Quartz
TMAE
H_2O
O_2
TMAE:
$E_{ion} = 5.3eV$
very reactiv with O_2
low vapour pressure
UV photons mean free path at 170 nm
this measurement C_2H_6 (40 Torr) + TMAE
Seguinot et al
Anderson
TMAE
λ [mm]
1cm Abs. length
⇒ 33°C
TMAE temperature [°C]
⇒ head detector!
to >40°C (105°F)

RICH – The Reality

- Center of ring depends on track angle $\Longrightarrow$ large detector surface
- good resolution of photon position $\Longrightarrow$ large number of "pixels" (100000)
- Spectrum of Cherenkov photons

$$\frac{dN}{d\lambda} = \frac{2\pi\alpha}{\lambda^2} L \sin^2\theta_c$$

  $\Longrightarrow$ Ultraviolet
- refractive index $n = n(\lambda) \Longrightarrow$ Chromatic dispersion
- Detection of UV-photons: convert photon in electron (photoeffect)
  1. small (up to a few thousand) number of pixels: Photomultipliers
  2. large number of pixels or area: Time Expansion Chambers with TEA or TMAE
- When using TEC: particle pass through the chambers: dE/dx
- When using TEC: response (memory) time limit rate

First RICH Example: The Omega RICH

WA89: A Hyperon Beam Experiment at the CERN-SPS Using the Omega Facility

Bologna Univ./INFN, CERN, Genoa Univ./INFN Grenoble Univ./IN2P3, Heidelberg MPI, Heidelberg Univ., Mainz Univ., Moscow Lebedev Phys. Inst.

Bologna

A. Forino, R. Gessaroli, P Mazzanti, A. Quareni-Vignudelli, F. Viaggi

CERN

F. Antinori, W. Beusch, J.P. Dufey, B.R. French, P. Grafström

Genoa Univ./INFN

M. Dameri, R.B. Hurst, B. Osculati, L. Rossi, G. Tomasini

Grenoble Univ./IN2P3

D. Barberis, C. Bérat, M. Buénerd, F. Charignon, J. Chauvin, J.T. Hostachy, Ph. Martin, M. Rey–Campagnolle, R. Touillon

Heidelberg MPIfK

E. Albertson, K.-H. Brenzinger, W. Brückner, F. Dropmann, S.G. Gerassimov, M. Godbersen, T. Kallakowsy, R. Michaels, S. Paul, B. Povh, K. Röhrich, A. Trombini, A. Wenzel, R. Werding

Heidelberg Univ.

J. Engelfried, F. Faller, J. Heintze, S. Kluth, S. Ljungfelt, P. Lennert, K. Martens, H. Rieseberg, H.-W. Siebert, A. Simon, G. Wälder

Mainz Univ., Inst. of Nucl. Physics

E. Chudakov, U. Müller, G. Rosner, H. Rudolf, B. Volkemer, Th. Walcher

Moscow Lebedev Phys. Inst.

M.I. Adamovich, Yu.A. Alexandrov, S.P. Kharlamov, L.N. Malinina, N.G. Peresadko, M.V. Zavertyaev



Counting gas: Ethan + TMAE,
1 KV/cm, 5 cm/μsec


Radiator
Strahl
10
9
8
7
6
1
2
3
4
5
80cm
170cm




conductive strips
Al_2O_3 substrate
electrodes for counting voltage
counting wire
a)
base plate of the counting module
drift field 1kV/cm
focusing field
counting wire
b)
gate open
gate closed

Nuclear Instruments and Methods in Physics Research A 343 (1994) 279–283
North-Holland

NUCLEAR INSTRUMENTS & METHODS IN PHYSICS RESEARCH Section A

Particle identification with the RICH detector in experiment WA89 at CERN **

U. Müller [a,*], J. Engelfried [b,1], S.G. Gerassimov [a,c], K. Martens [b], R. Michaels [a,3], H.-W. Siebert [b], G. Wälder [b]

[a] Institut für Kernphysik, Univ. Mainz, Germany
[b] Physikalisches Institut, Univ. Heidelberg, Germany
[c] Max-Planck-Institut für Kernphysik, Heidelberg, Germany

The RICH detector in the hyperon beam experiment WA89 at the CERN-SPS is used for identification of π, K and p/p̄ out of Σ⁻–N reactions. Methods for reduction of charged particle background in the detector are discussed. An algorithm for particle identification was developed and tested on a sample of Λ → pπ⁻ decays. A separation of p and π with 90% efficiency and a rejection by a factor of 10 or more at a momentum of 150 GeV/c was achieved.

1. Introduction

We report on algorithms used for particle identification with the upgraded Omega RICH detector [1] in the hyperon beam experiment WA89 [2] at the CERN-SPS.

Cherenkov light is generated in a nitrogen radiator ($n = 1.00029 \pm 10^{-5}$) of length $L \approx 5$ m and detected in a set of five drift chambers, covering a total active surface of 3.6×4.75 m^2 with a maximum drift path of 41 cm. Photoelectrons are counted on 1280 wires with a pitch of 2.54 mm, equipped with multihit TDCs. The overall spatial accuracy is $\sigma = 2.8$ mm for single electrons, corresponding to an angular resolution of 0.56 mrad [3]. The counting gas is ethane saturated with TMAE at 30°C. Fig. 1 shows an on-line display of one event in the RICH of the 1991 beamtime. This display contains the signals observed in the chambers, the particle impacts extrapolated from the spectrometer, and the predicted rings for the mass hypotheses π, K, and p. Also the momenta and charges of the tracks are given. Cherenkov photon signals along the predicted rings are clearly seen. We also note two half-rings in the centre from an out-of-time beam particle or e⁺e⁻ pair.

In the following, we present data analysis methods to reduce the background from charged tracks and other sources, and to identify particles with high efficiency and low probability of misidentification.

2. Background reduction

A charged particle traversing the drift chamber volume produces a few hundred electrons, which give a signal with high amplitude on several (typically three) adjacent wires. In addition, these large signals may produce electronic cross talk to neighbouring channels and signals due to δ rays or photon feedback. All these effects combined lead to a cluster of observed hits around the charged particle impact point.

In the raw data, information about a second discriminator threshold which is higher than the one used for single electron signals is available for each group of eight neighbouring wires [4]. This is used in the first step of background subtraction to suppress all hits with high amplitudes which may stem from a traversing

Particle Identification Algorithm

- only discrete particle masses: e, μ, π, K, p, Σ, etc.
- Track parameter and momentum known
  $\Longrightarrow$ Calculate ring radius for each hypothesis
- "Compare" measured and expected rings for each hypothesis with a maximum likelihood method
- for identification, make cuts on likelihood ratios

Second RICH Example: The SELEX RICH

The SELEX Collaboration

G.P. Thomas
Ball State University, Muncie, IN 47306, U.S.A.

E. Gülmez
Bogazici University, Bebek 80815 Istanbul, Turkey

R. Edelstein, S.Y. Jun, A.I. Kulyavtsev[1], A. Kushnirenko, D. Mao[1], P. Mathew[2], M. Mattson, M. Procario[3], J. Russ, J. You[4]
Carnegie-Mellon University, Pittsburgh, PA 15213, U.S.A.

A.M.F. Endler
Centro Brasiliero de Pesquisas Físicas, Rio de Janeiro, Brazil

P.S. Cooper, J. Kilmer, S. Kwan, J. Lach, E. Ramberg, D. Skow, L. Stutte
Fermilab, Batavia, IL 60510, U.S.A.

V.P. Kubarovsky, V.F. Kurshetsov, A.P. Kozhevnikov, L.G. Landsberg, V.V. Molchanov, S.B. Nurushev, S.I. Petrenko, A.N. Vasiliev, D.V. Vavilov, V.A. Victorov
Institute for High Energy Physics, Protvino, Russia

Li Yunshan, Mao Chensheng, Zhao Wenheng, He Kangling, Zheng Shuchen, Mao Zhenlin
Institute of High Energy Physics, Beijing, P.R. China

M.Y. Balatz[5], G.V. Davidenko, A.G. Dolgolenko, G.B. Dzyubenko, A.V. Evdokimov, M.A. Kubantsev, I. Larin, V. Matveev, A.P. Nilov, V.A. Prutskoi, A.I. Sitnikov, V.S. Verebryusov, V.E. Vishnyakov
Institute of Theoretical and Experimental Physics, Moscow, Russia

U. Dersch[6], I. Eschrich[7], I. Konorov[8], H. Krüger[9], J. Simon[10], K. Vorwalter[11]
Max-Planck-Institut für Kernphysik, 69117 Heidelberg, Germany

I.S. Filimonov[5], E.M. Leikin, A.V. Nemitkin, V.I. Rud
Moscow State University, Moscow, Russia

A.G. Atamantchouk, G. Alkhazov, N.F. Bondar, V.L. Golovtsov, V.T. Kim, L.M. Kochenda, A.G. Krivshich, N.P. Kuropatkin, V.P. Maleev, P.V. Neoustroev, B.V. Razmyslovich, V. Stepanov, M. Svoiski, N.K. Terentyev[12], L.N. Uvarov, A.A. Vorobyov
Petersburg Nuclear Physics Institute, St. Petersburg, Russia

I. Giller, M.A. Moinester, A. Ocherashvili, V. Steiner
Tel Aviv University, 69978 Ramat Aviv, Israel

J. Engelfried[4], A. Morelos
Universidad Autónoma de San Luis Potosí, San Luis Potosí, Mexico

M. Luksys
Universidade Federal da Paraíba, Paraíba, Brazil

V.J. Smith
University of Bristol, Bristol BS8 1TL, United Kingdom

M. Kaya, E. McCliment, K.D. Nelson[13], C. Newsom, Y. Onel, E. Ozel, S. Ozkorucuklu, P. Pogodin
University of Iowa, Iowa City, IA 52242, U.S.A.

L.J. Dauwe
University of Michigan-Flint, Flint, MI 48502, U.S.A.

M. Gaspero, M. Iori
University of Rome "La Sapienza" and INFN, Rome, Italy

L. Emediato, C.O. Escobar[14], F.G. Garcia[4], P. Gouffon, T. Lungov[15], M. Srivastava, R. Zukanovich-Funchal
University of São Paulo, São Paulo, Brazil

A. Lamberto, A. Penzo, G.F. Rappazzo, P. Schiavon
University of Trieste and INFN, Trieste, Italy


Selex (E781)
Proton Center Layout
W
S
N
E
Gas
House
PC3
PC4
BTRD
Photon 1
PW C
eTRD
Ring-Imaging Cherenkov
Hyperon Targetting
Magnet
Target,
Vertex
region
M1
DC
PW C
M2
HOD1
HOD2
Vee A
Vee B
Photon 2
Vee C
M3
PW C
Photon3
neutron
calorimeter
Elevator
0 m
10 m
20 m
30 m
40 m
50 m
60 m
Vertex Region
20 μm pitch
Beam Si
detectors
S4 Beam
Scintillator
20 μm pitch
VX Si detectors
25 μm pitch
VX Si detectors
Interaction
Veto (V5)
Scintillator
X [cm]
+2
0
-2
u y x
x y 1 u v x y 2 u v
x y 3 u v
x y 4 u v
x v 5 u x
Targets
Cu Diamond
Interaction
Scintillators
-20
-10
0
10
20
30
40
Z [cm]
50

ELSEVIER

Nuclear Instruments and Methods in Physics Research A 431 (1999) 53–69

NUCLEAR INSTRUMENTS & METHODS IN PHYSICS RESEARCH Section A

www.elsevier.nl/locate/nima

The SELEX phototube RICH detector

J. Engelfried[a,*,1], I. Filimonov[b,2,3], J. Kilmer[a,1], A. Kozhevnikov[c,3], V. Kubarovsky[c,3], V. Molchanov[c,3], A. Nemitkin[b,3], E. Ramberg[a,1], V. Rud[b,3], L. Stutte[a,1]

[a]*Fermi National Accelerator Laboratory, Batavia, IL, USA*
[b]*Moscow State University, Moscow, Russia*
[c]*Institute for High Energy Physics, Serpukhov, Russia*

Received 6 November 1998

Abstract

In this article, construction, operation, and performance of the RICH detector of Fermilab experiment 781 (SELEX) are described. The detector utilizes a matrix of 2848 phototubes for the photocathode to detect Cherenkov photons generated in a 10 m neon radiator. For the central region an N_0 of 104 cm^{-1}, corresponding to 13.6 hits on a $\beta = 1$ ring, was obtained. The ring radius resolution measured is 1.6%. © 1999 Published by Elsevier Science B.V. All rights reserved.

1. Introduction

The Fermilab experiment E781 (SELEX): a segmented large x_F Baryon spectrometer [1,2], which took data in the 1996/1997 fixed target run at Fermilab, is designed to perform high statistics studies of production mechanisms and decay physics of charmed baryons such as Σ_c, Ξ_c, Ω_c and Λ_c. The physics goals of the experiment require good charged particle identification to look for the different baryon decay modes. One must be able to separate π, K and p over a wide momentum range when looking for charmed baryon decays like $\Lambda_c^+ \to pK^-\pi^+$.

A RICH [3] detector with a 2848 phototube photocathode array has been constructed [4,5] to do this. The detector begins about 16 m downstream of the charm production target, with two analysis magnets with 800 MeV/c p_t-kick each in-between, and is surrounded by multi-wire proportional and drift chambers which provide particle tracking. The average number of tracks reaching the RICH is about 5 per event. First results from this detector can be found in Ref. [6].

Particle Identication I

Jlg.sty; ICFA2002 25Nov02. 53

* Corresponding author. Now at Instituto de Física, Universidad Autonoma de San Luis Potosí, Manuel Nava # 6, Zona Universitaria, 78240 San Luis Potosi, Mexico. Tel.: + 52-48-262362; fax: + 52-48-133874 e-mail; jurgen@fnal.gov.

[1] Work supported by the US Department of Energy under contract NO. DE-AC02-76CHO3000.

[2] Deceased.

[3] Supported by the Russian Ministry of Science and Technology.

SELEX RICH Vessel and Gas System



Vessel: 10.3 m long

2.4 m diameter ($50\,m^3$)

Gas: Neon @ 1 atm

closed volume ($\Rightarrow$ constant refractive index)

Filling:

- purge with CO_2 (≈ 1 day)
- freeze out CO_2, replace with Ne
- remove remaining O_2 and water
- started with 3 ppm O_2
- after 15 months: (20 ± 12) ppm



SELEX RICH Mirrors

Spherical, nominal 20 m Radius
16 hexagonal mirrors, 46 cm tip to tip

- Glass
  - low expansion glass (Schott Tempax), 10 mm thick.
  - Polished to 19.82 m $\pm$ 5 cm
  - Measured with Ronchi Method (NIMA 369 (1996) 69-78)
- Coating
  - Aluminum, with MgF_2 overcoating (Acton)
  - Reflectivity $> 85\,\%$ at 160 nm
- Mounting
  - 3 point mount
  - Ball bearing, double differential screw
  - Honeycomb panel with carbon fiber matrix
- Alignment
  - Theodolite with Laser in Center of Curvature
  - Vessel movable on wheels lateral to beam

Reprinted from

NUCLEAR INSTRUMENTS & METHODS IN PHYSICS RESEARCH
Section A

Nuclear Instruments and Methods in Physics Research A 369 (1996) 69–78

A method to evaluate mirrors for Cherenkov counters

Linda Stutte*, Jürgen Engelfried, James Kilmer

Fermi National Accelerator Laboratory, P.O. Box 500, Batavia, IL 60510, USA

Received 19 June 1995

The Ronchi Method



$$I = \frac{D \cdot Y}{D \mp G \cdot N_{\text{bands}}}$$

$$\frac{1}{S} + \frac{1}{I} = \frac{2}{R}$$

L. Stutte, J. Engelfried, J. Kilmer: *A Method to evaluate Mirrors for Cherenkov Counters.* Nuclear Instruments and Methods A369 (1996) 69, FERMILAB-PUB-95-138-E

Two Example Mirrors



The SELEX RICH Prototype Mirror



Analysis Results SELEX RICH Prototype Mirror



Image at the Film



Found Bands



Radius Variation vs Position



Analyzed Mirror Radii (cm)


A
VIEW A-A
BEAM DIRECTION


1
2
3
4
5
6
7
8
MIRROR



SELEX RICH Photon Detection

- Photomultiplier Holder
  - Aluminum plate, 2848 (89×32) holes
  - individual quartz windows as gas seal
  - aluminized mylar Winston cones
- Photomultipliers
  - $\frac{1}{2}$" diameter, Photocathode 10 mm
  - 608 Hamamatsu R760
  - 2240 FEU60 (with wavelength shifter)
  - all PM measured to find operating voltage
  - groups of 32 run on same HV
- High Voltage
  - Operating Voltage 900 V...1900 V
  - 6 HV Supplies
  - Zener Box (á la "Berkeley Cow"), 96 outputs
- Crates with Hybrid Chips
  - Hybrids contain Amplifier, Discriminator, diff. ECL Driver
- Readout: CROS PWC System
  - Integration time 170 nsec


10 cm
Aluminum HOLDER PLATE
Aluminized Mylar CONE
PHOTOTUBE
Mylar RING
1 inch
Quartz WINDOW


Particle Identication I

SELEX RICH PM Box



5700 lbs



trk	momnt	pid	pckge	stat	gam	bckg	e	muon	pion	kaon	p	sigma
1	71.4	5	rich	8	-1.00	0.00	0.79	1.00	0.88	0.00	0.00	0.00
2	-136.8	9	rich	8	-1.00	0.00	0.88	0.96	1.00	0.00	0.00	0.00
3	-38.1	9	rich	8	-1.00	0.00	0.00	0.06	1.00	0.00	0.00	0.00
4	50.0	8	rich	8	-1.00	0.00	0.24	0.81	1.00	0.00	0.00	0.00
5	-107.7	12	rich	8	-1.00	0.00	0.00	0.00	0.00	1.00	0.00	0.00

RUN 1755 EVENT 10000030 TUBES: 67



trk	momnt	pid	pckge	stat	gam	bckg	e	muon	pion	kaon	p	sigma
2	-81.9	9	rich	8	-1.00	0.00	0.75	0.96	1.00	0.00	0.00	0.00
3	-120.2	9	rich	8	-1.00	0.00	0.61	0.82	1.00	0.00	0.00	0.00
4	-22.5	3	rich	8	-1.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00
5	-88.1	15	rich	8	-1.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00

RUN 1755 EVENT 110000004 TUBES: 49



SELEX RICH Stability – Refractive Index



SELEX RICH Stability – N_0

$$N_{\rm ph} = N_0 \cdot L \cdot \sin^2 \theta_c$$



SELEX RICH Separation

Momentum of particles: $95\,\mathrm{GeV}/c - 105\,\mathrm{GeV}/c$



SELEX RICH Efficiency – Protons



SELEX RICH Efficiency – Kaons



SELEX RICH Efficiency – $D^0 \to K^{\mp}\pi^{\pm}$



Small statistic: The RICH is too good!!

A Current RICH: DIRC at BaBar

DIRC at BaBar

Detection of internally reflected Cherenkov light





DIRC at BaBar – Performance





Future in RICH and México: CKM RICHes

Future Use: CKM

Will use 2 RICHes to really measure velocity. Particle ID comes for free.



How Gaussian is the response?

A Study with SELEX single beam tracks

SELEX Standard Algortithm



Standalone Pattern recognition



Gaussian over nearly 5 orders of magnitude!

Good Spherical Mirror to measure Flat Mirror

Ronchigram of Spherical Mirror



The First Flat Mirror Prototype



First Ronchigrams of Flat Mirror Prototype





Only possible to measure part of surface (Geometry, Size of Spherical Mirror)

Only Center Part of Flat Mirror Prototype



Mirror rotated by 90° between the two pictures

Only Outer Parts of Flat Mirror Prototype



That's it.....

Summary

- Particle Identification (for charged particles) usually measures the velocity of the particle, identification is combined with the already known momentum.
- Transition Radiation Detectors mostly used in beamlines, but also to measure decay products (mostly electron–pion separation)
- Cherenkov effect is used Threshold Cherenkov Counters
- Cherenkov effect is used in RICH detectors
- RICHes are an established standard detector now, and have a bright future.